

Faster, Safer Weighing for Washdown Applications



Faster Weighing

Speed up your weighing operation by spending less time loading and unloading. Simply move the pallet jack or other vehicle into the scale's open area and lower the load onto the platform. There are no ramps to slow up the loading process.



Easier Cleaning

The stainless steel scale allows faster and easier washdown in sanitary applications. With the U-shaped platform, there is less surface area to clean. Built-in handles make it easy to lift the light-weight scale for cleaning the floor and underside of the scale.



Safer Operation

By eliminating ramps and pits, this U-shaped scale makes your weighing operation safer. Workers never need to strain to push heavy loads up an incline. The easy loading process means less chance of injuries and accidents.



Exceptional Versatility

Customize your scale to meet a variety of weighing needs. Attachments are available to widen the platform or convert it into a standard floor scale. These options enable you to weigh different sizes and types of loads.



PTA469 Pallet Scale

The PTA469 pallet scale is a low-profile scale that provides an excellent return on your investment. It delivers accurate, reliable weighing while standing up to constant use in tough environments. The U-shaped platform simplifies the job of loading pallets and containers onto the scale. There are no ramps or pits, so the scale costs less to install, saves floor space, and speeds up loading and weighing. Whether workers use a forklift truck, pallet jack, or powered walkie to load the scale, they never need to drive up a ramp or across the scale platform. Eliminating ramps reduces the opportunity for injuries and accidents. Because wheeled vehicles never drive across the platform, there is less of the wear and tear that can shorten a floor scale's life.

PTA469 Pallet Scale

Specifications

Standard Platform Size	48x48, 48x60, and 60x60 inches (1219x1219, 1219x1524, and 1524x1524 mm)
Available Capacities	1000 lb / 600 kg, 2500 lb / 1200 kg, and 5000 lb / 2500 kg
Platform Height	3 ⁵ / ₁₆ inches (84 mm)
Standard Construction	Type 304 stainless steel
Load Cell Type	Four 350-ohm load cells; hermetically sealed stainless steel
Load Cell Suspension	Stainless steel rocker-foot assembly
Junction Box	Stainless steel IP69K
End Loading	100% end loading
Standard Operating Temp.	14°F to 104°F (-10°C to 40°C)
Metrological Approvals	Pending
Hazardous Area Approvals	FM, CSA, Ex, ATEX
Shipping Weight	215, 230, and 240 lb (98, 104, and 109 kg)
Standard Instrument Cable Length	25 feet (7.6 meters)


Features

Benefits

Top-of-Floor Installation	No need for ramps or pits.
U-shaped Design	Easy to load with a pallet jack.
Stainless Steel Construction	Suitable for washdown.
Hermetically Sealed Load Cells	Maximum protection in wet and corrosive environments.
Locating Plates	Position the scale securely.
Integral Lift Handles	Easy to lift the scale for cleaning and moving.
Optional Wheel Kit	Easy to move scale to new location.



Bumper Guard



Leg Wideners



Side Rails



Load Plate



Wheel Kit



Integral Lift Handle

The Right Scale for Your Application

Choose from a range of options to customize a pallet scale to meet the specific needs of your application.

Options

- Wheel kits for easy portability
- Bumper guards protect the scale from damage
- Side rails make loading easier
- Leg wideners for weighing larger pallets
- Load plates provide a full-sized platform
- Locating plates prevent scale movement
- Free-standing columns
- Instrument mounting brackets
- Factory calibration for fast startup
- Type 316 stainless steel

www.mt.com/floorscale

For more information

Produced in a facility that is



Mettler-Toledo, LLC

1900 Polaris Parkway
Columbus, Ohio 43240
Tel. (800) 786-0038
(614) 438-4511
Fax (614) 438-4900

Specifications subject to change without notice.
© 2012 Mettler-Toledo, LLC
07/2012
FS03534.0E